


HIDDEN ROUND 19



COLOUR TEMP. (K)	2700	3000
5W RIBBON	LS-HR19-0527	LS-HR19-0530
10W RIBBON	LS-HR19-1027	LS-HR19-1030
19W RIBBON	LS-HR19-1927	LS-HR19-1930

Luminous Flux (lm):	360 / 720 / 1440 lms p/mtr
Colour Temperature/s (K):	2700 / 3000
Power Consumption (W):	5 / 10 / 19
Voltage (V):	12 / 12 / 24
Current (I):	n/a
Beam Angle (°):	200
Colour/Finish:	Clear anodised aluminium with opal diffuser
Applications:	Vanities, joinery, task lighting, pelmets and coves.
Features:	Soft general lighting, low glare diffuser, small profile with high output, minimal aesthetic. Drivers ordered separately and available in 01-10V dimmable or non-dimmable.
Lamp Type:	3528 LED Ribbon
Lifespan (hrs):	35,000
Fixture Size:	19.5 x 19.8mm High
CRI:	> 90
IP Rating:	20 (IP65 available on request)
Mounting:	Suspended + surface mount with screw fixing

 **the lighting guild**™

Phone +61 2 9098 8999

Email info@thelightingguild.org

Visit www.thelightingguild.org

PO Box 6209 West Gosford NSW 2250 Australia