


HIDDEN SLIM



COLOUR TEMP. (K)	2700	3000
5W RIBBON	LE-HS-0527	LE-HS-0530
10W RIBBON	LE-HS-1027	LE-HS-1030
19W RIBBON	LE-HS-1927	LE-HS-1930

Luminous Flux (lm):	360 / 720 / 1440 lm p/mtr
Colour Temperature/s (K):	2700 / 3000
Power Consumption (W):	5 / 10 / 19W/mtr
Voltage (V):	12 / 24 / 24
Current (I):	N/A
Beam Angle (°):	170°
Colour/Finish:	Silver anodised with satin diffuser
Applications:	Suitable replacement for a T5 fluorescent, joinery, vanities, under bench lighting, coffers and bulkheads. (NB: 5 and 10W options are suitable for limited applications.)
Features:	Ultra slim profile, extremely low maintenance. Drivers ordered separately and available in non-dimmable, 0-10V or phase dimmable. Also available in 2100 and 2400K on request.
Lamp Type:	3528 LED Ribbon
Lifespan (hrs):	35,000
Fixture Size:	14 x 7mm Deep
CRI:	< 90
IP Rating:	44
Mounting:	Surface and recessed

 **the lighting guild™**

Phone +61 2 9098 8999
 Email info@thelightingguild.org
 Visit www.thelightingguild.org
 PO Box 6209 West Gosford NSW 2250 Australia