

# SNOOT 2 - LOW GLARE RECESSED DOWNLIGHT



COLOUR TEMP. (K)	2700	3000	Warm to Dim
STANDARD (IP40)	SU-DLS-0927	SU-DLS-0930	AL-DLS-12WD
EXTERIOR (IP44)	SU-DLSE-0927	SU-DLSE-0930	AL-DLSE-12WD

<b>Luminous Flux (lm):</b>	810 / 820 / 810
<b>Colour Temperature/s (K):</b>	2700 / 3000 / Warm to Dim (Dims to 1800K)
<b>Power Consumption (W):</b>	9 / 9 / 12
<b>Voltage (V):</b>	240
<b>DC Drive Current (I):</b>	210 / 210 / 500mA
<b>Beam Angle (°):</b>	36 / 36 / 38°
<b>Colour/Finish:</b>	Matt White or Satin Black
<b>Applications:</b>	Accent lighting
<b>Features:</b>	Low glare, minimal trim, low maintenance, includes phase dimmable driver c/w flex and plug. Diginet dimmers recommended. DALI driver available on request. Exterior model includes zinc plated / powder coated reflector and is suitable for Zone 1 wet areas.
<b>Lamp Type:</b>	Authentic CREE COB LED
<b>Lifespan (hrs):</b>	40,000
<b>Fixture Size:</b>	Ø 81 x 103 mm High
<b>CRI:</b>	> 90
<b>IP Rating:</b>	IP40 / IP44(Exterior)
<b>Mounting:</b>	Recessed with Ø 76mm Cut Out

 **the lighting guild™**

Phone +61 2 9098 8999  
 Email [info@thelightingguild.org](mailto:info@thelightingguild.org)  
 Visit [www.thelightingguild.org](http://www.thelightingguild.org)  
 PO Box 6209 West Gosford NSW 2250 Australia